



⑨	SCREW	#4-40 2.3*45MM,BLACK PVC	2	PCS
⑧	OUTER MOLDED	LIGHT BLUE 45P PVC	26	G
⑦	OUTER MOLDED	GREEN 45P PVC	26	G
⑥	OUTER MOLDED	RED 45P PVC	26	G
⑤	OUTER MOLDED	BLACK 45P PVC	26	G
④	INTER MOLDED	LDPE	26	G
③	CONNECTOR	RCA MALE,GOLD FLASH SHELL	3	PCS
②	CONNECTOR	HDB15PIN MALE,BLACK INSULATOR	1	PCS
①	CABLE	UL2919 (30AWG*1C+AL+S)*3C+PAPER OD:8.0MM BLACK JACKET	3	M
NO.	MATERIAL	DESCRIPTIONG	QTY.	UNIT

REQUIREMENTS:

1:100% short and open testing.

2:Test conditions

DC300V /10MS

Insulation resistance 10MΩ(Min)

Conduction resistance 5Ω(Max)

Ltremref	Quantity	Title/Name,designation,material,dimension etc			Article No./Reference		
Designed by	Checked by	Approved by - date MARCH 4.2012	File name HDB 15P/M-RCA/M=3 L=3M	Date MARCH 4.2012	Scale FREE		
			26-1543				
			26-1543		Edition 1	Sheet 1/2	